

2020 TILE COLLECTIONS







The onset of the new decade marks the testament of Mariwasa's commitment towards going circular - a clean manufacturing that minimizes environmental harm. With more than fifty years in the ceramic tile industry, Mariwasa has prospered as a trusted home solution-provider for Filipino families. Committed to delivering unwavering quality products such as ceramic and porcelain tiles, sanitary wares and fittings, and tile adhesive, Mariwasa embraces technological innovations that not only forward efficiency but also sustainability -- an advocacy which Mariwasa upholds as a social responsibility.

Driven by this cause for this year's launch of the new tile designs, Mariwasa's visionary team of designers honed the "ECO-WAY" collection inspired by nature sustainability in the contemporary world. We proudly introduce you this year's subthemes, **KU1-TURE**, **NATURIZED** and **BE-LIVE**, which evoke the balance of modern, ergonomic aesthetics and organic, nature-inspired style. Get inspired with the artistry of each new tile series as you go through the pages of this catalog.

KU1°TURE

Salingawi sa Makabagong Panahon

This series is a homage to our local roots intertwined within the modern, contemporary times. Designs range from vintage, realistic wood and rock patterns to free-flowing, geometric curves and patterns that easily blend in any room scenes.

NATURIZED

Naturized is an expression of nature's beauty while adapting the contents of modern technology by creating abstract forms. This series showcases linear, abstract patterns and minimalistic nature forms in earth tones, guaranteed to be the final touch of finesse and sophistication that you need for your home.

BE-LIVE

A firm dedication for wellness and sustainability.

B is for Biophylic – connectivity to the natural & healthy environment;

E is for Eco-friendly – practices that help conserve resources;

live - for we are referring to all forms of life on earth.

Perfect for bohemian and oriental-inspired interior, this series endows your space with a relaxing atmosphere through its classic wood and rock patterns that instantly connects you with nature.




Tips & Reminders



Recommended Tile Usage

RATING LEGEND	CLASSIFICATION	TILE GROUPINGS	AREAS OF APPLICATION	
CLASS 1	LIGHT TRAFFIC	Suited to areas that are walked on essentially with soft soled footwear or bare feet without scratching dirt.	Residential bedrooms, bathrooms, powder rooms	
CLASS 2	LIGHT / MEDIUM TRAFFIC	Suited to areas that are walked on soft soled or normal footwear with occasional small amounts of scratching dirt.	Living rooms, dining rooms, study rooms	
CLASS 3	MEDIUM TRAFFIC	Suited to areas that, with normal footwear, are walked on more often with small amounts of scratching dirt.	Residential kitchens, halls, corridors, terraces, balconies, toilets, hospital rooms	
A CLASS 4 HEAVY TRAFFIC		Suited to areas that are walked on by regular traffic with some scratching dirt so that the conditions are more severe than Class 3.	Entrances, commercial kitchens, hotels, exhibition halls, offices	
CLASS 5 EXTRA HEAVY TRAFFIC		Suited to areas that are subject to severe pedestrian traffic over sustained periods with some scratching dirt, so that the conditions are the most severe for which glazed floor tiles may be suitable.	Shopping centers, airport concourses, hotel foyers, public walkways, industrial applications	


Shade Variation Scheme





KU1°TURE 60x60 cm MANABU Series With anti-slip feature on structured mould








MANABU Brown F2



MANABU Brown F3

KU1°TURE




*Suggested tile installation for ELMO









KU1°TURE

40x40 cm TERRENO Series With anti-slip feature on structured mould 40x40 cm CERVANTES Series With luster effect on structured mould



TERRENO Beige



TERRENO Brown





CERVANTES Grey



CERVANTES Brown

NATURIZED







NATURIZED 60x60 cm ORIELE Series



ORIELE Ochre



ORIELE Red

BE•LIVE









BE•LIVE
60x60 cm ANJI Series
With sinking effect







ANJI Brown

KU1°TURE









■ ESQUINA Beech

ESQUINA Brown

QUIRINO Ochre

QUIRINO Red







BRAGANZA Brown



BRAGANZA Grey




MANABU Brown F1



MANABU Brown F2




MANABU Brown F3



BE•LIVE 40x40 cm VIGOR Series

Printed on structured mould





BE•LIVE 40x40 cm FERROCK Series With anti-slip feature on structured mould







FERROCK Red



FERROCK Grey



BE•LIVE

60x60 cm TERRA Series I 30x60 cm RAMMED Series
With anti-slip feature Printed on structured mould



TERRA White



TERRA Grey



TERRA Brown



RAMMED Brown



RAMMED Blue

NATURIZED









NATURIZED

30x60 cm BOUNCE Series | I


Beige

With sinking effect

30x60 cm BIT Series

Ivory

Glaze technology on structured mould




White

Grey

KU1°TURE







NATURIZED 60x60 cm HUB Series







HUB Beige

HUB Coral

HUB Grey

BE•LIVE





KU1°TURE 60x60 cm ESQUINA Series

Printed on structured mould







ESQUINA Brown

NATURIZED



BE•LIVE







KU1°TURE 60x60 cm BRAGANZA Series I 30x60 cm NUEVA Series



BRAGANZA Brown



BRAGANZA Grey



NUEVA Beige



NUEVA Grey

Floor Tile Packaging Specifications

	SIZE		WE	IGHT	F	PACKIN	G		SQM	
СМ	INCH	THICKNESS (mm)	WT/PC (kg)	WT/20'FCL (t)	PCS/CTN (pcs)	CTN/PLT (ctn)	PLT/20'FCL (plt)	PC/SQM (pcs)	SQM/PLT (sqm)	SQM/ 20'FCL
40 x 40	16 x 16	8.35	2.80	19.6	9	52	15	6.25	74.8	1,123.2
30 x 60	12 x 24	10.35	3.70	19.5	6	44	20	5.6	47.5	949.6
60 x 60	24 x 24	10.35	7.30	19.6	4	28	24	2.8	40.3	966.9

Icon Legend

g GLOSSY	wall wall	HALLWAY/LOBBY	BEDROOM
МАТТЕ	ANTI-SLIP	LIVING ROOM	BATHROOM
r RUSTIC	RECTIFIED	O DINING ROOM	OUTDOOR
FLOOR & WALL	STRUCTURE MOULD	KITCHEN	POOL / POND
FLOOR	DIGITAL TILES		

Floor Tile Technical Specifications

CHARACTERISTICS	STANDARDS	MARIWASA SPECIFICATIONS	
Properties	Group Bllb	8.35	
Dimension and surface quality			
Length and width		±0.5%	
Thickness		±5.0%	
Straightness of sides	ISO 10545-2	±0.5%	
Rectangularity		±0.6%	
Center curvature		±0.5%	
Edge curvature		±0.5%	
Water absorption	ISO 10545-3	6% < E ≤ 10%	
Breaking strength			
Thickness ≥ 7.5 mm	100 40545 0	Not less than 800 N	
Thickness < 7.5 mm	ISO 10545-3	Not less than 500 N	
Modulus of rupture		≥ 18 N/mm2	
Abrasion resistance	ISO 10545-7	Minimum Class 1	
Crazing resistance	ISO 10545-11	Required	
Resistance to staining	ISO 10545-14	Minimum Class 3	
Chemical resistance, low concentrate acids and alkalis		Minimum Class GB	
Chemical resistance, high concentrate acids and alkalis Chemical resistance, household and swimming pool salts	ISO 10545-13		



Unit 802 Fort Legend Tower, 3rd Avenue corner 31st Street, Bonifacio Global City, Taguig City, Philippines 1634 Tel. No.: +632 717-6900 Fax. No.: +632 836-9864 / 836-9866 hotline@mariwasa.com www.mariwasa.com













March 2020



*Color of tiles in this print may vary slightly due to the printing process.

*Final color selection should be made from actual tile samples.

*The information in this print may be modified or updated by Mariwasa without prior notice.

For inquiries, ask TYLER:

7717-6901 (Loc. 2278)







Follow us:







Visit us: www.mariwasa.com